

GOSLING SPIRIT™

CANNING SYSTEMS FOR CRAFT DISTILLERIES



Start canning affordably with small batch, entry-level packaging for cocktails, spirits, coffee, infused drinks and more.

Package your sparkling cocktails, still liquors and other high-proof and ready-to-drink beverages in single-serve 100-milliliter steel cans or slim aluminum cans.

The Gosling *Spirit* allows distilleries and craft beverage producers to expand product portfolios to include convenient, consumer-friendly cans of premium carbonated and non-carbonated beverages.



STEEL & ALUMINUM CAN FLEXIBILITY

Package in a range of slim body aluminum cans as well as 100 mL steel cans to take advantage of the right can types for your drinks.



EXPAND YOUR MARKETS

Portable and infinitely recyclable, cans are the perfect option for on-the-go consumers where plastic or glass may not be suitable or sustainable.



READY TO CAN

User-friendly operation and plug-and-play features allow you to fill small volumes with ease from a variety of pressurized or unpressurized vessels.

SPEED UP TO
14 CANS
PER MINUTE



The Gosling *Spirit* canning system makes your professional small-volume canning run a reality, and Wild Goose helps you get it done *fast*.



LEARN
MORE

+1 720.406.7442 | Sales@WildGooseFilling.com
www.WildGooseFilling.com

PROUDLY
MANUFACTURED IN
COLORADO, USA.

LOCAL SERVICE WORLDWIDE.

 JOIN THE FLOCK.



GOSLING SPIRIT™

CANNING SYSTEMS FOR CRAFT DISTILLERIES

SPEED UP TO:

Based on 100 mL can at optimal conditions

HEADS	1
cans/min	14
cans/hr	840
cases/hr	35
bbl/hr	2.5
gal/hr	78.7
hL/hr	3.0
m ³ /hr	0.3
L/hr	298

CAN SIZES:

- 100 mL 202 body steel can
- 150 mL 202 body aluminum can
- 187 mL 202 body aluminum can
- 200 mL 202 body aluminum can
- 250 mL 202 body aluminum can

LID TYPE: 200 end

CONFIGURATION: Tabletop system with adjustable leveling feet

OPTIONAL ACCESSORIES:

- Multiflow Control Kit
- DO Buster™ CO2 Tunnel
- Pre- and Post-Rinse
- GooseNeck™ Infeed
- Liquid Nitrogen Dosing
- Mobile Cart
- Advanced Tool Kit
- Spare Parts Kit
- SPA Treatment (Service Partnership Agreement)

INSTALLATION: Onsite installation by certified Wild Goose technician recommended

WARRANTY: Standard 1-year warranty; Extended warranty available

REPEATABLE WILD GOOSE SEAMING

Patented Wild Goose seaming technology, specially engineered to provide consistent seams for steel and aluminum cans, helps prevent flavor loss, spoilage and leaks.

INTEGRATED INTERFACE

Full-color touchscreen interface gives fast access to controls, settings and information through approachable, user-friendly menus.

COMPACT SIZE

With a small footprint and modular accessory options, the ultracompact Gosling *Spirit* fits in small spaces and stows away easily when not in use.

BUILT FOR LONGEVITY

Durable, high-quality Wild Goose construction assures machine reliability cycle after cycle.

PRECISION FILLING

Controlled flow methods deliver regulated, accurate fill volumes from tank or keg to minimize waste and meet packaged yield specifications.



DISSOLVED OXYGEN CONTROLS

Automated CO2 purging, foam controls, smooth transfers, optional DO Buster™ CO2 Tunnel and repeatable seaming work together to control the impact of dissolved oxygen on your beverage shelf life and flavor.

	STANDARD SYSTEMS	EUROPEAN SYSTEMS
DIMENSIONS	44 in L x 26 in W x 41-43 in H	112 cm L x 66 cm W x 104-109 cm H
DECK HEIGHT	Entry and exit height of 12-14 inches above base surface	Entry and exit height of 30.5-35.5 cm above base surface
WEIGHT	275 lb	125 kg
POWER	• Single-phase 13A @ 115VAC, 50/60 Hz • Single-phase 200V-240V	Single-phase 200V-240V
COMPRESSED AIR	Clean, dry compressed air required at 6.5 scfm @ 95-100 psi in accordance with ISO 8573-1:2010 (-:4:-). Dew Point < 37° F	Clean, dry compressed air required at 185 L/min @ 6.5-7.0 bar in accordance with ISO 8573-1:2010 (-:4:-). Dew Point < 3° C
CO2	Required at 12-25 psi dependent on optional accessories	Required at 0.8-1.7 bar dependent on optional accessories