

ACCUMULATION PACK-OUT CONVEYOR

FOR EVOLUTION SERIES™ CANNING SYSTEMS



Manage your flow of cans with compact inline conveyance integrated at the end of your canning system.

The Accumulation Pack-Out Conveyor allows finished cans of any size to continuously accumulate at the outfeed of your Evolution Series canning system for easier assembly into multipacks, cases, or other packaging.



6-PACK ACCUMULATION

Index cans into six-pack-friendly rows for easy handle application and case packing.



VARIABLE SPEED

Adjust the conveyor speed to match velocity with your canning system and case-packing process.



CAN FLEXIBILITY

Use the Accumulation Pack-Out Conveyor for any size and diameter can with no changeover needed.



TECHNICAL SPECIFICATIONS

DIMENSIONS: 76 in (193 cm) L x 22 in (56 cm) W x 71 in (180 cm) H

DECK HEIGHT: Adjustable 44 in - 46 in (112 cm - 117 cm)

WEIGHT: 185 lb (84 kg)

POWER:

- Single-phase 4A @ 115VAC, 60 Hz
- Single-phase 2A @ 230VAC, 50/60 Hz

SPEED: Adjustable

CAN SIZE COMPATIBILITY: Any can diameter or height

CONFIGURATIONS:

- Straight outfeed from canning line
- 90-degree outfeed from canning line

MACHINE COMPATIBILITY:

- Evolution Series single-lane canning systems
- Evolution Series dual-lane canning systems

INSTALLATION: Self-installed



LEARN
MORE

+1 720.406.7442 | Sales@WildGooseFilling.com
www.WildGooseFilling.com

Wild Goose Filling
633 CTC Blvd Ste 100
Louisville, CO 80027 USA

European Offices
Barcelona, Spain
Trento, Italy