

TECHNICAL SPECIFICATIONS

	M2	M4	M6
Filling Heads / Crowners	2	4	6
Production Rates (up to) <small>(based on 12 oz/355 mL bottle at optimal conditions)</small>	12 bottles/min 30 cases/hr 2.2 bbl/hr 67.5 gal/hr 2.6 hL/hr 0.26 m ³ /h 258 L/hr	30 bottles/min 75 cases/hr 5.4 bbl/hr 169 gal/hr 6.4 hL/hr 0.64 m ³ /h 639 L/hr	40 bottles/min 100 cases/hr 7.3 bbl/hr 225 gal/hr 8.5 hL/hr 0.85 m ³ /h 850 L/hr
Bottle Diameter Capability	2.1"-7.0" diameter (53 mm x 178 mm)	2.1"-5.0" diameter (53 mm x 127 mm)	2.1"-3.0" diameter (53 mm x 76 mm)
Machine Dimensions	5.5' L x 3.5' W (1676 mm x 1067 mm)	5.5' L x 3.5' W (1676 mm x 1067 mm)	5.5' L x 3.5' W (1676 mm x 1067 mm)
Power	17A @ 115VAC, 56/60 Hz 9A @ 230VAC, 56/60 Hz	17A @ 115VAC, 56/60 Hz 9A @ 230VAC, 56/60 Hz	17A @ 115VAC, 56/60 Hz 9A @ 230VAC, 56/60 Hz
Compressed Air	15 cfm @ 90 psi (25 m ³ /h @ 6.2 bar)	15 cfm @ 90 psi (25 m ³ /h @ 6.2 bar)	15 cfm @ 90 psi (25 m ³ /h @ 6.2 bar)
CO ₂ Requirements <small>(Based on single purge for 12 oz. bottles)</small>	4 cfm @ 40 psi	8 cfm @ 40 psi	12 cfm @ 40 psi

CONFIGURATIONS

STANDARD MODEL

Locking Casters	Included	Included	Included
Adjustable Leveling Feet	Optional	Optional	Optional
Big Crown Hopper	Optional	Optional	Optional
Guarding	Optional	Optional	Optional

CE-CERTIFIED MODEL CE

Locking Casters	Included	Included	Included
Adjustable Leveling Feet	Optional	Optional	Optional
Big Crown Hopper	Optional	Optional	Optional
Guarding	Included	Included	Included

BOTTLING SYSTEMS

Upgradeable 2.2 to 7.3 bbl/hr counterpressure bottling systems that simplify your packaging operation



UP TO
40
BOTTLES PER MINUTE

Rinser: Semi-Automatic
Purge & Fill: Automatic
Crowning: Automatic

