

GOOSENECK INFEED™

Feed your Gosling™.



SIMPLIFIED GOSLING™ INFEED

The GooseNeck Infeed streamlines can loading for your Wild Goose Gosling canning system.



REDUCED LABOR

Minimizes ongoing infeed labor by allowing you to load 10 cans at once



TIME SAVINGS

Provides approximately 60-second buffer time between each reload of cans



Quality craft canning,
simplified.



GOOSENECK INFEED™

Feed your Gosling.



MULTIPLE CAN SIZES

Accommodating multiple can sizes, the GooseNeck Infeed allows Gosling QuickChange™ operators to shift between can sizes during various product runs. No adjustments or change parts are needed for most can body sizes.

EFFICIENT LOADING

A gentle back pressure weight continuously pushes cans from the GooseNeck into the Gosling system. The handle of the back pressure weight provides the operator an at-a-glance reload indicator.

LOW MAINTENANCE

The GooseNeck does not require pneumatic or electrical supply to operate. Simple, sleek construction offers easy cleaning and is designed to stand up to long-term wear.

COMPACT DESIGN

With a direct-mount design that conserves floor space, the GooseNeck Infeed keeps your Gosling operation compact. Attaching or detaching the GooseNeck is simple and can be completed in less than 5 minutes.

TECHNICAL SPECIFICATIONS

Compatibility: All Gosling canning systems: Standard, QuickChange™, Nitro™

Capacity: About 10 cans per load; approximately 60-second reload cycle

Can Sizes: 202, 204, 211 can body diameters up to 6.6"
(168 mm) can height

Dimensions: 24" L x 6.5" W x 28.5" H
(60 cm L x 16 cm W x 73 cm H)

Weight: 11 lb (5 kg)



Wild Goose Filling
633 CTC Boulevard, Suite 100
Louisville, CO 80027 USA

+1 720.406.7442
www.WildGooseFilling.com
Sales@WildGooseFilling.com

